# REPORT DOCUMENTATION PAGE OMB No. 0704-0188 Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 3. DATES COVERED (From - To) 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE Technical Paper 5a. CONTRACT NUMBER 4. TITLE AND SUBTITLE 5b. GRANT NUMBER ease see 5c. PROGRAM ELEMENT NUMBER 5d. PROJECT NUMBER 6. AUTHOR(S) 5503 5e. TASK NUMBER 000P 5f. WORK UNIT NUMBER ×49×07 8. PERFORMING ORGANIZATION 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) REPORT 10. SPONSOR/MONITOR'S 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) ACRONYM(S) Air Force Research Laboratory (AFMC) 11. SPONSOR/MONITOR'S AFRL/PRS NUMBER(S) 5 Pollux Drive Edwards AFB CA 93524-7048 Mease see alta 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited. 13. SUPPLEMENTARY NOTES 14. ABSTRACT 20030206 078 15. SUBJECT TERMS 19a. NAME OF RESPONSIBLE 16. SECURITY CLASSIFICATION OF: 17. LIMITATION 18. NUMBER OF ABSTRACT **OF PAGES PERSON** Leilani Richardson 19b. TELEPHONE NUMBER a. REPORT b. ABSTRACT c. THIS PAGE

Unclassified

Unclassified

Unclassified

(include area code) (661) 275-5015

Form Approved

# MEMORANDUM FOR PRS (Contractor/In-House Publication)

FROM: PROI (TI) (STINFO)

25 Aug 2000

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-AB-2000-169
G. Scriven, N. Gat (OKSI), R. Lyons (ERC), "Monocular Passive Ranging Sensitivity Analysis and Error Minimization" (Abstract)

2001 Meeting of MSS Specialty Group on MD-SEA (Statement A) (Monterey, CA, 30 Jan – 01 Feb 01) (Submission Deadline: 25 Aug 00)

1. This request has been reviewed by the Foreign Disclosure Office for: a.) appropriateness of distribution statements.) military/national critical technology, c.) export controls or distribution restrictions, d.) appropriateness for release to a foreign nation, and e.) technical sensitivity and/or economic sensitivity.  Comments:	
· · · · · · · · · · · · · · · · · · ·	
Signature	Date
2. This request has been reviewed by th and/or b) possible higher headquarters and Comments:	
Signature	Date
b.) appropriateness of distribution state. e.) parallel review completed if required Comments:	e STINFO for: a.) changes if approved as amended, ment, c.) military/national critical technology, d.) economic sensitivity, d, and f.) format and completion of meeting clearance form if required
Signature	Date
appropriateness of distribution statement national critical technology, and f.) data Comments:	
	APPROVED/APPROVED AS AMENDED/DISAPPROVE
	PHILIP A. KESSEL Date Technical Advisor Propulsion Science and Advanced Concents Division

# Monocular Passive Ranging Sensitivity Analysis and Error Minimization

Gordon Scriven<sup>1</sup>, Dr. Nahum Gat<sup>1</sup>, Dr. Robert Lyons<sup>2</sup>

Opto-Knowledge Systems Inc. (OKSI)

2ERC, Inc Edwards AFB

### **Abstract**

Monocular Passive Ranging (MPR) may allow accurate target range estimation even when active measurements or multiple views are not possible. Due to the inherent nature of the MPR solution, the uncertainties may degrade the utility of the range estimate. Proper spectral band selection is essential for error minimization. The study goes beyond the traditional CO2 red spike band for MPR. Featured in the current analysis are the following absorption bands: O2 at 0.76 microns, CO2 at 2.0 and 4.3 microns, and Ozone at 4.7 and 9.6 microns. More importantly, a sensitivity analysis procedure is presented that both minimizes these errors and provides an uncertainty assessment of the range measurement. The result is an improved ranging capability and a more accurate characterization of the intervening atmosphere. The solution technique is applied to an actual HALO/IRIS measurement (Black Brant). However, the MPR software is designed to provide real-time range estimations and atmospheric compensation. A research version of the code has been developed to support integration of this technology into the HALO/IRIS upgrade.

#### Outline

- 1. Introduction
- 2. Solution Technique
- 2.1 relevant physics
- 2.2 spectral band selection
- 3. Sensitivity Analysis
- 3.1 automatic differentiation (AD)
- 3.2 identifying key input parameters
- 4. Error Minimization
- 4.1 pre-flight onboard measurements(local atmosphere, star measurements, ground measurements)
- 4.2 response surface (from AD)
- 4.3 recursion analysis
- 4.4 uncertainty estimation
- 5. Data Comparison
- 5.1 Black Brant measurement from HALO/IRIS
- 5.2 data vs. model range estimation
- 6. Integration into HALO/IRIS Upgrade
- 6.1 HALO/IRIS instrumentation description and capabilites
- 6.2 Software architecture (HALO/IRIS + MPR)
- Recommendations
- Summary

### Comments

# State-of-the-art Advancement:

Automatic Differentiation (AD) is an emerging technology that is currently under utilized in the field of remote sensing and related phenomena. AD can be applied to existing models for sensitivity analysis. It can also be integrated into the model development itself for improved robustness and more expedient programming.

### Key results:

The utilization of multi-spectral sensors, combined with a pre-flight measurement process, extend the envelope of MPR applicability. Previous techniques have broken down for up-looking scenarios. The technique presented in this paper will provide improved ranging capabilities even for some up-looking view geometries.

An accurate MPR technique provides the target trajectory and atmospheric compensation. Both of these are needed for improved target typing, discrimination and tracking.